

Central **EDGE**

The Central Edge includes onboard booster heater.



RackStar Conveyor Dishwashers

Double-wall insulated doors. Double Rainbow Rinse® with arched rinse arm. EnergyGuard™ controls cuts idle energy use. Stainless steel construction. 208V or 230V, single or three phase. Please specify.

- Uses 0.35 gallons of water per rack
- 223 racks per hour capacity
- 19³/₄"H door opening
- Fully automatic including auto-fill, self-cleaning arms and self-draining pump
- Available with Energy Recovery at an additional cost. Please call for details.



Free Start Up
Call 800.222.5107 for details

Free Onboard Booster Heater

FREE SHIPPING



LIMITED ONE YEAR PARTS & LABOR WARRANTY

OUTSTANDING ADDITIONAL SIX MONTH WARRANTY WITH CERTIFIED INSTALLATION. CALL FOR DETAILS.

Model#	Description	Overall WxDxH	Your Cost
RACKSTAR 44			
670-053	High Temperature	54"x30"x64 ¹ / ₂ "	\$19490.06
670-054	Chemical Sanitizing	54"x30"x64 ¹ / ₂ "	17001.00
RACKSTAR 66			
670-164	High Temperature	64"x30"x69"	25294.00
670-165	Chemical Sanitizing	64"x30"x69"	25294.00

Value Series

Hood Type High Temperature Dishwasher

Internal cavity and exterior panels are constructed with 304 series stainless steel. 208/240V. Available in Single or Three phase. 28³/₈"Wx29"Dx56⁷/₈"H with door closed. 28³/₈"Wx29"Dx74"H with door open.

- 30 racks an hour on a 2 minute cycle
- 20 racks an hour on a 3 minute cycle
- Manual pump drain for multiple installation applications, including elevated drains
- 185° sanitizing rinse every cycle, max 50° rise
- Low 0.79 gallon water usage per rack
- Removable wash and rinse arms for easy cleaning
- Triple filtering system captures soil and debris



ONE YEAR PARTS AND ONE YEAR ON-SITE LABOR WARRANTY

FREE SHIPPING

Model#	Wt.	Your Cost
226-072	220#	\$5749.



DynaTemp® High Temperature Dishwasher

17¹/₄" door opening that washes up to 57 racks per hour. Sani-Sure™ feature assures proper rinse water temperature. Other features include auto-fill/auto-start, delime and vent fan controls, self-draining stainless steel pump, multi-cycle timer and digital controls. Interchangeable scrap baskets are included. 30³/₁₆"Wx29¹/₂"Dx61"H.

- Uses 0.69 gallons of water per rack
- Built-in 70°F booster heater
- Single point connections for utilities
- Stainless steel construction
- Available with optional ventless and energy recovery

FREE SHIPPING

ONE YEAR PARTS AND LABOR WARRANTY



Model#	Wt.	Your Cost
670-052	350#	\$9106.65



Ventless High Temperature Single Rack Dishwashers

Internal condensing system minimizes vapor eliminating need for a hood. Heat recovered from wash cycle heats water for final rinse reducing energy and water costs. Auto-fill and auto-start. Stainless steel construction. Built-in 70°F rise booster. Delime/manual wash switch. Self-draining stainless steel pump. Cold water connection only. Field convertible from straight through to corner and vice versa.

ONE YEAR PARTS AND LABOR WARRANTY

FREE SHIPPING



STANDARD HOOD

Available in 208V (single or three phase), 230V (single or three phase) or 460V (three phase).

- Uses 0.89 gallons of water per rack
- 39 racks per hour capacity
- 17¹/₄" door opening
- Automatic 87 second cycle

Model#	WxDxH	Wt.	Your Cost
670-039	25 ¹ / ₄ "x30 ¹ / ₂ "x82"	350#	\$11269.

HIGH HOOD

Extended 15 second high-temperature rinse. Available in 208V (single or three phase), 230V (single or three phase) or 460V (three phase).

- Uses 1.36 gallons of water per rack
- 37 racks per hour capacity
- 20³/₄"x27" opening accommodates full-size sheet pans and up to 60 quart mixing bowls
- Totally automatic 92 second cycle

Model#	WxDxH	Wt.	Your Cost
670-040	25 ¹ / ₄ "x30 ¹ / ₂ "x93"	435#	\$12977.

HOBART

Ventless Single Rack Dishwasher

Recaptures heat from the rinse cycle to heat the water for the next wash. Internal condensing system reduces the amount of steam to virtually nothing. Door actuated start. Revolving wash and rinse arms. Stainless steel construction with solid-state controls. Built-in booster heater (70° rise). NSF listed for effective cleaning. Available in three phase.

- Uses 0.74 gallons of water per rack
- 40 racks per hour capacity
- 1-, 2-, 4- or 6-minute cycles
- 29¹/₄"Wx35"Dx69"H

ONE YEAR PARTS AND LABOR WARRANTY

FREE SHIPPING



Model#	Door Opening Height	Voltage	Wt.	Your Cost
492-076*	17"	208V	451#	\$17237.72
492-221	27"	208/240V	494#	20509.77
492-222	27"	480V	494#	21506.10

*Single or three phase