




Hot Food Drop-In Wells

Individual infinite controls, except #200-080 and #200-081, which have thermostatic controls. NSF listed.
 • Stainless steel • 23⁷/₁₆"Dx8¹¹/₁₆"H overall
 • Fully insulated 6¹/₄"H wells install in tables and countertops and accommodate standard steam table pans

Model#	Wells	Width	Cutout WxD	Your Cost
WITHOUT DRAINS AND MANIFOLDS				
200-080	1	15"	13 ³ / ₄ "x21 ³ / ₄ "	\$487.85
200-083	2	29 ³ / ₄ "	28 ⁵ / ₈ "x22 ³ / ₈ "	1306.80
200-050	3	44 ¹ / ₁₆ "	43"x22 ¹ / ₂ "	1717.10
200-052	4	58 ¹ / ₂ "	57 ³ / ₈ "x22 ¹ / ₂ "	2241.80
200-054	5	72 ⁷ / ₈ "	71 ³ / ₄ "x22 ¹ / ₂ "	2806.65
200-056	6	87 ¹ / ₄ "	86 ¹ / ₈ "x22 ¹ / ₂ "	3873.10
WITH DRAINS AND MANIFOLDS				
200-081	1	15"	13 ³ / ₄ "x21 ³ / ₄ "	535.70
200-084	2	29 ³ / ₄ "	28 ⁵ / ₈ "x22 ³ / ₈ "	1384.90
200-051	3	44 ¹ / ₁₆ "	43"x22 ¹ / ₂ "	1865.60
200-053	4	58 ¹ / ₂ "	57 ³ / ₈ "x22 ¹ / ₂ "	2628.45
200-055	5	72 ⁷ / ₈ "	71 ³ / ₄ "x22 ¹ / ₂ "	3211.45
200-057	6	87 ¹ / ₄ "	86 ¹ / ₈ "x22 ¹ / ₂ "	4351.60



ONE YEAR PARTS AND LABOR WARRANTY **FREE SHIPPING**

VOLTAGE OPTIONS	
120V*	1500W
208V/240V	1200W/1600W

*Only available for single well units

VOLLRATH Induction Dry Well Hot Drop-Ins

Save time by eliminating need for water or drain installation. Dry operation means this unit does not get hot. Install on any surface with minimal clearance. Better consistency and less food waste with precise temperature control. Each well fits one full-size, or two half-size, pans at either a 4" or 2¹/₂" depth. 26"Dx15"H. NSF listed. Requires use of Vollrath Induction-Ready Pans. Will not work with traditional stainless steel pans.

Model#	Wells	Width	Voltage Options	Your Cost
913-776	1	15"	120V 208/240V	\$1378.00
913-777	2	28 ¹ / ₄ "	120V 208/240V	2544.00
913-778	3	41 ¹ / ₂ "	120V 208/240V	3815.40
913-779	4	54 ³ / ₄ "	208/240V	5087.25
913-780	5	68"	208/240V	6359.05
913-781	6	81 ¹ / ₄ "	208/240V	7631.00



Model#	Type	Depth	Your Cost
913-782	Full-Size	4"	\$26.49
913-783	Full-Size	2 ¹ / ₂ "	20.19
913-784	Half-Size	4"	18.99
913-785	Half-Size	2 ¹ / ₂ "	12.89



Refrigerated Drop-In Cold Wells

Fully insulated. Drain included. Accommodates standard steam table pans up to 6"H. Meets NSF 7 standard. Field adjustable temperature control. Illuminated on/off switch mounted on side of unit near compressor.
 • Heavy duty stainless steel
 • 28"Dx23³/₁₆"H. Capacity based on 12"Wx20"D pans.
 • 120V. 6' cord and plug included.



Refrigerated Drop-In Wells

NSF 7 standard. Electronic control assembly can be mounted to either side of the condensing unit or remotely mounted up to four feet from unit. Auto defrost is activated through an advanced electronic controller programmed at customer location. Adjustable condensing unit can rotate 90° or 180° for venting adjustments and flexibility at installation. Pair with Hatco heated wells for fully integrated look. 1" drain.
 • Aluminized steel construction
 • 27"Dx25¹/₂"H
 • 120V. 5' cord and plug included.



ONE YEAR PARTS AND LABOR WARRANTY **FREE SHIPPING**

Model#	HP	Width	Pan Capacity	Wt.	Your Cost
200-082	1/5	19 ¹ / ₂ "	(1) Full-Size	121#	\$2590.50
200-085	1/4	32"	(2) Full-Size	179#	2907.30
200-059	1/4	46 ¹ / ₈ "	(3) Full-Size	203#	3071.75
200-060	1/4	59"	(4) Full-Size	233#	3274.70
200-095	1/3	72 ¹ / ₄ "	(5) Full-Size	327#	3560.70

Model#	HP	Width	Pan Capacity	Wt.	Your Cost
315-361	1/4	19"	(1) Full-Size	133#	\$2928.20
315-362	1/4	32"	(2) Full-Size	175#	3117.95
315-363	1/4	45"	(3) Full-Size	213#	3344.55
315-364	1/3	58"	(4) Full-Size	235#	3581.60
315-365	1/2	71"	(5) Full-Size	270#	3886.85
315-366	1/2	84"	(6) Full-Size	313#	4188.40

Value Series



Hot Food Drop-In Wells

Remote control panel. All units include drains for wet or dry application. Indicator lights. NSF listed. Choose from economical infinite controls heating.

- Stainless steel construction
- Fully insulated wells install in tables and countertops and accommodate standard steam table pans
- 25"Dx10¹/₁₆"H overall

ONE YEAR WARRANTY

VOLTAGE OPTIONS	
120V*	1100W
240V	1100W

Single phase. *Not available on units with four or more wells.

Model#	Wells	Width	Wt.	Your Cost
INFINITE CONTROLS				
435-052	2	32 ⁵ / ₁₆ "	46#	\$1369.
435-053	3	47 ⁵ / ₈ "	58#	1660.05
435-054	4	62 ⁵ / ₁₆ "	70#	1971.90
435-055	5	78 ¹ / ₂ "	82#	2569.00
435-056	6	93 ³ / ₁₆ "	94#	3029.00
THERMOSTATIC CONTROLS				
435-057	2	32 ⁵ / ₁₆ "	46#	1369.00
435-058	3	47 ⁵ / ₈ "	58#	1660.05
435-059	4	62 ⁵ / ₁₆ "	70#	1971.90
435-060	5	78 ¹ / ₂ "	82#	2569.00
435-061	6	93 ³ / ₁₆ "	94#	3029.00

Value Series

Refrigerated Drop-In Cold Wells

18 gauge stainless steel, self-rimmed top. Black marine-edge prevents spills and contains moisture. Gasket for sealing unit to countertop. Fully self-contained condensing unit. 1" drain and gate valve. Fully insulated. Precision digital thermostat for exact temperature control. Meets NSF 7 standards. 25¹/₂"Dx8"H wells.
 • Stainless steel construction • 26³/₄"Dx9³/₁₆"H overall
 • 1/3 HP. 120V. 6' cord and plug included.

Model#	Width	Pan Capacity	Wt.	Your Cost
435-070	20"	(1) Full-Size	163#	\$2122.20
435-071	33 ¹ / ₂ "	(2) Full-Size	187#	2269.00
435-072	47"	(3) Full-Size	207#	2490.75
435-073	60 ¹ / ₂ "	(4) Full-Size	229#	2774.25
435-074	74"	(5) Full-Size	251#	3250.80
435-075	87 ¹ / ₂ "	(6) Full-Size	273#	3489.00

ONE YEAR WARRANTY



Heated Drop-In Wells

Thermostatic controls. Separate On/Off rocker switch and temperature dial. Unique design allows quick change of element or thermostat if needed.

- EZ locking hardware for quick installation. Please select a side or bottom drain.
- Stainless steel construction
- Fully insulated wells
- 23⁵/₈"Dx9⁵/₈"H overall

VOLTAGE OPTIONS	
Specify 208V or 240V	
Wells	Watts
2	2415
3	3615
4	4815
5	6015
6	7215

Single phase, field convertible to three phase

ONE YEAR ON-SITE PARTS AND LABOR WARRANTY, PLUS ONE ADDITIONAL YEAR PARTS-ONLY WARRANTY ON ALL METAL SHEATHED HEATING ELEMENTS

Model#	Wells	Width	Wt.	Your Cost
MANIFOLD DRAIN				
315-413	2	29 ¹ / ₂ "	77#	\$1298.55
315-414	3	43 ³ / ₂ "	100#	1720.99
315-415	4	57 ¹ / ₂ "	136#	2327.60
315-416	5	71 ¹ / ₂ "	166#	2909.50
315-417	6	85 ¹ / ₂ "	190#	3616.80
MANIFOLD DRAIN WITH AUTO-FILL				
315-418	2	29 ¹ / ₂ "	87#	1629.10
315-419	3	43 ¹ / ₂ "	112#	2052.05
315-420	4	57 ¹ / ₂ "	133#	2658.70
315-421	5	71 ¹ / ₂ "	167#	3231.25
315-422	6	85 ¹ / ₂ "	190#	3930.85