

Insulated Cabinets

METRO

Humidity-Controlled Holding and Proofing Cabinets

Continuously monitors both temperature and humidity. Low water sensor and low temperature alarm. Non-marking polymer bumper and drip trough combination.

Water reservoir is removable and can be replaced. 120V, 1,950 watts. 7 1/2' cord included. 30"Wx36 3/8"D.

- Heavy duty stainless steel exterior
- Field reversible doors
- Separate controls for temperature and humidity
- Digital controls, +70°F to +200°F temperature range, relative humidity range of 0%-95%
- 5" casters, two with brakes
- Universal wire slides hold a variety of pans



PAN CAPACITIES			
3" slide spacing			
Model#	18"Wx26"D	12"Wx20"Dx2 1/2"H	
340-348	18	34	
340-349	17	32	
340-350	8	16	
340-351	8	16	

ONE YEAR LIMITED WARRANTY

FREE SHIPPING

Model#	Description	Wt.	Your Cost
HALF HEIGHT—44 3/4" TALL, INCLUDES 8 SLIDE PAIRS			
340-350	Solid Door	200#	\$5249.
340-351	Clear Door	197#	5149.
FULL HEIGHT—74 3/4" TALL, INCLUDES 18 SLIDE PAIRS			
340-348	Solid Door	400#	6299.
340-349	Clear Dutch Doors	410#	6142.

METRO

Half-Height Holding and Transport Cabinets

Indicator lights. Removable slides and control panel. 37"H. 120V. 900 watts. 6' cord and plug included.

- Aluminum exterior with stainless steel interior
- Magnetic catch holds door shut, includes travel latch and kick latch for hands-free opening
- Adjustable, thermostatically controlled temperature
- Up to 180°F temperature range
- 5" non-marking casters, two with brakes



FREE SHIPPING

PAN CAPACITIES			
2 1/2" Slide Spacing			
Model#	18"Wx26"D	12"Wx20"D	
340-326	—	9	
340-327	9	—	

Model#	WxD	Wt.	Your Cost
340-326	21 1/4"x24 3/4" 110#		\$1899. ONE YEAR LIMITED WARRANTY
340-327	27 1/4"x30 3/4" 128#		2289.

METRO

Holding and Transport Cabinets

Aluminum interior and high density polyethylene Insulation Armour™. Cool-to-touch exterior with molded-in hand-holds on all four corners. Polymer high-strength magnetic pull latch with lever-action release. 120V. 2,000 watts. 7 1/2' cord and plug included. 27 5/8"Wx31 1/2"D. Doors have a 180° swing and are field-reversible. Solid doors are fully insulated with 1" fiberglass, double panel. Lexan doors have an extruded aluminum powder coated frame with a .90" polycarbonate window. **Full height cabinets** come with dutch doors.

- Aluminum construction with durable polymer exterior
- Recessed controls
- Adjustable digital thermostat, +80°F to +200°F temperature range
- 5" casters, two with brakes



Solid Door
340-413

Lexan Door
340-415



ONE YEAR LIMITED WARRANTY

Model#	Slide Type	Slide Spacing	Wt.	Solid Door	Lexan Door
HALF HEIGHT CABINETS—44"H OVERALL, INCLUDE 8 SLIDE PAIRS					
340-469	Fixed Wire	3"	142#	\$2052.	\$2160.
340-471	Universal Wire	Adjustable*	150#	2156.	2268.
340-470	Lip Load	1 1/2"	145#	2220.	2336.
3/4 HEIGHT CABINETS—59"H OVERALL, INCLUDE 14 SLIDE PAIRS					
340-466	Fixed Wire	3"	173#	2215.	2331.
340-468	Universal Wire	Adjustable*	191#	2328.	2448.
340-467	Lip Load	1 1/2"	186#	2398.	2522.
FULL HEIGHT CABINETS—71"H OVERALL, INCLUDE 18 SLIDE PAIRS					
340-413	Fixed Wire	3"	270#	2448.	2578.
340-415	Universal Wire	Adjustable*	283#	2572.	2706.
340-414	Lip Load	1 1/2"	278#	2649.	2787.

*Slides are adjustable in 1/2" increments.
*Weights shown are for solid door units
For maximum number of pan slides, visit website for spec sheets.

FREE SHIPPING



PAN CAPACITIES (18"WX26"D)			
Cabinet Height	Fixed Wire	Lip Load	Universal
1/2	8	17	8
3/4	14	27	14
Full	17	34	17

Central EXCLUSIVE

Economy Proofing and Holding Cabinet

Mechanical controls with LED display. 120V. 1,500 watts. Cord and plug included.

- Aluminum construction
- Clear Polycarbonate door
- Separate controls for temperature and humidity
- Heat Mode: 80°F-185°F temperature range, Proof Mode: humidity range is from 30% to 100%
- Set of four 5" casters, two with brakes
- 1 1/2" slide spacing

FREE SHIPPING



PAN CAPACITIES	
18"Wx26"D	Slide Spacing
36	1 1/2"

Model#	WxDxH	Wt.	Your Cost	ONE YEAR REPLACEMENT WARRANTY
01H-028	23 1/8"x32 1/2"x67 1/2"	175#	\$1699.	



VULCAN

Holding and Transport Cabinets

Welded steel frame. Recessed side mounted lift handles. Forced air heating system. 120V. 1,500 watts. 8' rear mounted cord, cord wrap and plug. 27 1/4"Wx33"D.

- Stainless steel construction
- Adjustable thermostat, up to +195°F temperature range (up to +190°F on **Model #515-892**)
- 5" heavy duty casters, two swivel with brakes and two rigid (**Model #515-481** has 3" casters)
- 1 1/2" slide spacing

ONE YEAR PARTS AND LABOR WARRANTY
LIFETIME WARRANTY ON HEATING ELEMENTS

FREE SHIPPING

Model#	Description	Pan Slides Included	Ht.	Wt.	Your Cost
515-481	Solid Door	5	30 1/2"	173#	\$2430.00
515-262	Solid Door	5	40"	198#	3075.00
515-482	Solid Door	10	59 1/4"	270#	3625.00
515-237	Dutch Doors	10	65 1/4"	297#	4035.00
515-892	Dutch Doors	15	69 1/4"	337#	5359.90

