



CNF0201 • CNF0202 Countertop Nugget Ice Maker & Dispenser

Models CNF0201AL CNF0201A CNF0202AL CNF0202A Three dispense settings are standard: ice only, water only, or ice and water. *

Ice Machine Electric

CNF0202

115/60/1. (230/50/1 also available.) 115/60/1 ice machines are factory pre-wired with a 6' (180 cm) power cord and NEMA 5-15P-plug configuration. 230/50/1 ice machines are factory pre-wired with a 6' (180 cm) power cord only, no plug is supplied.

Total ampacity: Air-cooled: 10.3 amps. Maximum fuse size: Air-cooled: 15 amps.

HACR-type circuit breakers can be used in place of fuses.

Specifications

BTU Per Hour: 2,300 (average) Compressor:

Nominal rating: 1/3 HP Refrigerant: R404A

Operating Limits:

- Ambient Temperature Range: 45°-110°F (7.2°-43.3°C)
- Water Temperature Range: 45°-90°F (7.2°-32°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

- New bite-sized nugget boasts 85% ice content* with only 15% water offering one of the best nugget ratios for maximum cooling and minimal drink dilution.
- Up to 315 lbs. (143 kgs) standard daily ice production including ice and water content.
- New DuraTech™ front panel for easy cleaning and reduced hardwater staining in the dispense area.
- Only 16.25" (41.28 cm) wide by 24.00" (61.00 cm) deep by 35.00" (89.00 cm) tall on the RNS12 and 42.00" (107.00 cm) tall without legs; legs sold separately.
- Trouble-free ice dispensing. Simply place cup under chute and activate.
- Two ice activation options: activation arm or touchless.
- Dispense opening (10.50"/ 26.67 cm) from grate to chute maximizes clearance for tall containers.
- · Larger drain pan minimizes ice spillage.
- Blue LED light provides dispense visibility for rooms with limited ambient light.
- · Water and drain connections in back or bottom of unit for flush mounting.
- · Manitowoc's patented cleaning technology manages the cleaning process from start to finish.

CNF0201



Ice Shape

Nugget ice consists of small pieces ranging from 3/8" to 1/2" in width and length on average. Offers a 85% ice to water ratio with a softer, chewable texture while still providing maximum cooling effect and great dispensibilty.











COMPANY WITH QUALITY SYSTEM

2110 South 26th Street Manitowoc, WI 54220 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







		Ice Production 24 Hours		Power kWh/ 100 lbs.	
Model	Ice Shape	70°Air/50°F Water 21°Air/10°C Water	90°Air/70°F Water 32°Air/21°C Water	@ 90°/70°F 32°/21°C	
CNF0201A	nugget	315 lbs.	222 lbs.	6.69	
		143 kgs	101 kgs		
CNF0202A	nugget	315 lbs.	222 lbs.	6.69	
		143 kgs	101 kgs		
Water usage/100 lbs./45.4 kgs of Ice					
Potable Water: 12 gallons, 45.4 liters					

[&]quot;A" following model number indicates "Air" condensing unit.

Space-Saving Designs



CNF0201	CNF0202
35.00"	42.00"
89.00 cm	107.00 cm
16.25"	16.25"
41.30 cm	41.30 cm
24.00"	24.00"
61.00 cm	61.00 cm
10 lbs.	20 lbs.
4.5 kgs	9.1 kgs
	35.00" 89.00 cm 16.25" 41.30 cm 24.00" 61.00 cm 10 lbs.

^{*}Height without legs. Legs sold separately: K-00345.

Air Flow Front View Air in right, air out top.



Initiate ice, off and clean operations with simple upfront selector switch. No need to remove front panel.

Front Access



*Height includes 6" legs

© Electrical Entrance

CNF0201/202 42.00" (107.00 cm) 35.00" (89.00 cm) 12.50" (31.80 cm) **24.00**" (61.00 cm) 16.25" (41.30 cm) (A) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet B 3/4" (1.91 cm) Bin Drain

MINIMUM INSTALLATION CLEARANCE -

Top: 24" (60.96 cm); Sides: 8" (20.32 cm); Back: 5" (12.7 cm); Bottom: 0" (0 cm).

Stand offers a solution when there is no counter space available for an CNF0201 or 202 unit.

Kit Number	WxDxH	Shipping Weight
K 00453	22.2 x 29.2 x 36"	100 lbs
K-00453	56.4 x 74.2 x 76.2 cm	50 kgs

Lever-activated or Touchless Dispensing*



CNF0201L

CNF0202L



CNF0202

*Select at time of purchase. K-00377 can be used to convert from lever-activated to touchless sensing.

2110 South 26th Street Manitowoc, WI 54220 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 6550 03/18

