

DUNNAGE RACKS

Stationary & Mobile

- **Efficient Storage:** The low profile of Focus dunnage racks makes it easy to store large, bulky items off the floor without taking valuable shelf space.
- **Removable Wire Mat:** Fits top support frame. Lifts off for thorough cleaning. Offset wire design raises mat above post caps, preventing items from snagging or tearing.
- **Design:** Provides fast, secure assembly without the use of any special tools.
- **Available Finishes:** Chrome-plated or green epoxy coated finish.
- **Heights:** Stationary dunnage racks are 13 1/2" high including cap and leveling feet. Mobile dunnage racks are 12 1/2" high.



Stationary Dunnage Racks

- **Convenient:** Lower 3 sided support frame is open in front – no need to move the rack to clean beneath it. Open wire grid minimizes dust and moisture accumulation on mat.
- **Leveling Feet:** Compensate for surface irregularities.

Mobile Dunnage Racks

- **Ease of Movement:** Two swivel casters and two swivel/brake casters provide excellent maneuverability plus manageability. Casters are 5" (127 mm), non-marking polyurethane tread, designed for heavy-duty use.
- **Construction:** Top and lower support frames are made of 1" square tubing. Removable offset mat constructed of 5/16" (8.0 mm) diameter wire.



DUNNAGE RACKS Stationary & Mobile

Job _____

Stationary Dunnage Racks With Wire Mat



Width		Length		Approx Pkd. Wt.		Item No.	Item No.
(in.)	(cm)	(in.)	(cm)	(lbs.)	(kg)	Chrome Plated	Green Epoxy
18	45.7	36	91.4	31.0	14.1	FFSDR1836CH	FFSDR1836GN
18	45.7	48	121.9	38.8	17.6	FFSDR1848CH	FFSDR1848GN
18	45.7	60	152.4	47.4	21.5	FFSDR1860CH	FFSDR1860GN
24	61	30	76	31.3	14.2	—	FFSDR2430GN
24	61	36	91.4	36.7	16.7	FFSDR2436CH	FFSDR2436GN
24	61	48	121.9	46.0	20.9	FFSDR2448CH	FFSDR2448GN
24	61	60	152.4	56.3	25.6	FFSDR2460CH	FFSDR2460GN

Maximum distributed static load capacity 1600 lbs. on 36" wide shelves & 1300 lbs. capacity on 48" & 60" wide shelves.

Mobile Dunnage Racks With Wire Mat



Width		Length		Approx Pkd. Wt.		Item No.	Item No.
(in.)	(cm)	(in.)	(cm)	(lbs.)	(kg)	Chrome Plated	Green Epoxy
18	45.7	36	91.4	39.7	18.1	FFMDR1836CH	FFMDR1836GN
18	45.7	48	121.9	47.6	21.6	FFMDR1848CH	FFMDR1848GN
18	45.7	60	152.4	56.1	25.5	FFMDR1860CH	FFMDR1860GN
24	61	30	76	36.6	18.5	—	FFMDR2430GN
24	61	36	91.4	45.4	20.7	FFMDR2436CH	FFMDR2436GN
24	61	48	121.9	54.8	24.9	FFMDR2448CH	FFMDR2448GN
24	61	60	152.4	65.0	29.6	FFMDR2460CH	FFMDR2460GN

Maximum distributed static load capacity 800 lbs..