

EXTRA WIDE REACH IN FREEZERS

Full Door	Half Door
FS-1D-S1-EW	FS-1D-S1-EW-HD
FS-2D-S1-EW	FS-2D-S1-EW-HD
FS-3D-S1-EW	FS-3D-S1-EW-HD
FSA-1D-S1-EW	FSA-1D-S1-EW-HD
FSA-2D-S1-EW	FSA-2D-S1-EW-HD
FSA-3D-S1-EW	FSA-3D-S1-EW-HD

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

VICTORY ULTRASPEC™

FEATURING: **SecureTemp**
1.0™

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

There are NO software or monthly monitoring fees.
Optional add on kits are available for additional units.

STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- V-Temp™ Electronic Control System
- LED Lights with Proximity Door Switch Activates Interior Lighting
- Expansion Valve Technology
- 20 Gauge, Stainless Steel Doors
- Dual Speed, Energy Efficient, EC Fan Motors
- Santoprene Door Gaskets with Exclusive 2 Year Warranty
- Stainless Steel Breaker Strips
- High Performance, Balanced, Top-Mounted Refrigeration
- Environmentally Safe, R-134A Refrigerant
- Plasticized Evaporated Fin Coils
- Non-Electric Condensate Evaporator
- Foamed In-Place Polyurethane Insulation
- Heavy-Duty Cylinder Locks
- Self-Closing Doors With 120° Hold Open Feature
- Cam-Lift Hinges, Guaranteed For Life
- Ergonomically Correct Door Handles, Guaranteed For Life
- S & SA Series Have 6" High Adjustable Stainless Steel Legs
- Hinged Front Shroud Makes Condenser Cleaning Easier
- One Piece, Snap-In Magnetic Door Gasket(s)
- Anti-Condensate Door Perimeter Heaters
- Stainless Steel Interior Door Liner
- Three (3) Epoxy Coated Wire Shelves Per Cabinet Section
- Cord and Plug (see electrical data for details)



FS-2D-S1-EW

OPTIONS & ACCESSORIES

- Change Door Swing
- Remote Models
- Correctional Facility Options
- Stainless Steel Case Back & Shroud
- Stainless Steel Shelves
- 6" Overall Height Casters (set of 4)
- Exterior Laminate Décor
- Adjustable Tray & Pan Slides
- Optional Voltages



CABINET CONSTRUCTION

The cabinet front and doors are constructed of heavy gauge, polished stainless steel to maintain an attractive appearance after years of heavy use. Polyurethane foam insulation throughout ensures the ultimate in energy efficiency. The front shroud lifts up for easy access when cleaning the condenser unit.

DOOR CONSTRUCTION

The doors are heavy gauge, polished stainless steel with a stainless steel interior liner. Each door is provided with a cylinder lock and ergonomically correct vertical handle. The door hinges are self-closing and have a hold-open feature at 120° which facilitates product loading. Proximity switches energize the recessed interior incandescent lighting when the door is opened. Humidity control wires around the door jamb prevent condensation from forming on the front of the cabinet in high humidity environments. The wires are concealed by a high impact, non-conducting thermal breaker cap.

REFRIGERATION SYSTEM

All components of the high efficiency, air-cooled, self-contained refrigeration system are mounted on top of the cabinet out of the food storage zone providing greater storage space. Environmentally friendly R-134a refrigerant is efficiently metered by an expansion valve providing a constant, safe operating temperature and quick "recovery" under the most demanding conditions. The hermetically sealed systems are designed to operate at 38°F. Each cooling coil has plasticized fin coils to resist food acids and dual-speed EC fan motor(s) for greater cooling capacity and efficiency. All condensate water is disposed of automatically by the energy efficient, non-electric condensate evaporator.

INTERIOR STORAGE ARRANGEMENTS

Each cabinet section is provided with three heavy-duty, epoxy coated wire shelves. The shelves are adjustable in one inch increments. A wide door opening allows for the use of a variety of optional pan slide configurations including 18" x 26" and 12" x 20" pans.

V-TEMP™ CONTROL SYSTEM

The easy to use V-TEMP™ Control is standard. This durable, water resistant microprocessor monitors and controls the entire temperature maintenance process. It includes an ON/OFF switch, manual defrost, interior light switch, LED temperature indicator in °C or °F, a HI/LO audio/visual temperature alarm, power supply interruption, door ajar and "clean condenser" alarms. A manager's "lock-out" feature is provided to safeguard predetermined control settings. A HAACP Event Indicator/Memory feature announces and records up to nine (9) alarm events. Unique to the V-TEMP™ are two standard modes of operation:

SUPERCOOL - Provides a lower "set-point" refrigeration condition for a set period of time when food has just been loaded into the refrigerator and needs to be quickly brought back down to a safe temperature.

ENERGY SAVING - The cabinet automatically reverts to the energy saving mode when there are no door openings for four hours.

A **FLEXTAMP** mode of operation is available as an option. FLEXTAMP provides the ability to select a unique temperature from 28°F to 40°F. This optional feature is ideal for seasonal menu changes and items with specific temperature requirements for dairy, meat, fish or poultry.

CHARACTERISTICS	1 Section	2 Section	3 Section
Net Capacity	24.4	52	79.6
Width, Overall (in.)	31 1/4	58 3/8	85 1/2
Depth, Overall (inc. Handles)	35	35	36 1/2
Depth, Door(s) Open 90°	58 1/4	58 1/4	59 5/8
Clear Door Width (in.)	22 1/2	22 1/2	22 1/2
Clear Half-Door Height (in.)	25 3/8"	25 3/8"	25 3/8"
Clear Full-Door Height (in.)	55 1/4	55 1/4	55 1/4
Height Overall (inc. 6" legs)	84 1/4"	84 1/4"	84 1/4"
No. Full/Half Doors	1F, 2H	2F, 4H	3 F, 6H
No. of Shelves	3	6	9
Shelf Area (sq. ft.)	17.6	36.1	54.3

ELECTRICAL DATA

Cabinet Voltage	115/60/1	115/60/1	115/60/1
Feed Wires	2	3	3
Condensing Unit Voltage	115/60/1	209-230/60/1	208-230/60/1
NEMA Plug	5-15P	NO	NO
Total Amperes	10.9	12.2	14.9

NOTE: Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

REFRIGERATION DATA

Condensing Unit Size	1/2HP	3/4 HP	1 HP
Refrigerant	R-404a	R-404a	R-404a

CRATED DIMENSIONS	Height	Weight	Depth	Cu. Ft.	Lbs
One Section	83	36	44	76.08	335
Two Section	83	63	44	133.15	525
Three Section	84	90 3/4	44 3/4	197.41	645

* Remote units use R-404A refrigerant standard and come with 6" legs

NOTE: In order to provide peak operating performance the cabinet must have a 2 inch all around clearance and 12 inches above the top of the condensing unit. This ensures an adequate air supply and space for routine maintenance and/or service if required.

