

## WINE COOLERS

WC-1D-S1  
WC-2D-S1

- Equipped with Secure-Temp 1.0™ Technology™
- 3 Year Parts & Labor Warranty Plus an Additional 2 Year Compressor Warranty
- Exclusive 2 Year Warranty on Santoprene Door Gaskets

**VICTORY ULTRASPEC™**  
FEATURING: **SecureTemp™**  
1.0

Secure-Temp 1.0™ is the industry's first and only full service temperature monitoring solution for your kitchen. Secure-Temp 1.0™ is standard on all Victory models and is HACCP compliant & meets NAFEM's data protocol.

**There are NO software or monthly monitoring fees.**  
Optional add on kits are available for additional units.

## STANDARD FEATURES

- Secure-Temp 1.0™ Technology
- V-TEMP™ Electronic Control System
- High Performance, Balanced, Top-Mounted Refrigeration
- Environmentally Safe R-134a Refrigerant
- Energy Efficient, Dual-Speed EC Evaporator Fan Motor(s)
- Plasticized Evaporator Fin Coils
- Non-Electric Condensate Evaporator
- Foamed-in-Place Polyurethane Insulation
- Heavy Duty Cylinder Locks
- Self-Closing Doors with 120° Hold Open Feature
- Cam-Lift Hinges, Guaranteed for Life
- Ergonomically Correct Door Handles, Guaranteed for Life
- 6" Legs Standard
- Hinged Front Shroud Makes Condenser Cleaning Easier
- Proximity Door Switch Activates Interior Lighting
- One Piece, Snap-In Magnetic Door Gasket(s)
- Anti-Condensate Door Perimeter Heaters
- LED Lighting
- Energy Saving Thermal Breaker Caps, Guaranteed for Life
- Fully Extractable Wine Racks
- • Cord and Plug (see electrical data for details)



**WC-1D-S1**

## OPTIONS & ACCESSORIES

- Remote Models
- Stainless Steel Case Back & Shroud
- 6" or 3" Casters
- Optional Voltages: 220/50/1, 220/60/1



3779 Champion Blvd—Winston-Salem, NC 27105

PH: (888) 845-9800 - Fax: (800) 253-5168

sales@victoryrefrigeration.com www.victoryrefrigeration.com

## CABINET CONSTRUCTION

The cabinet front and doors are constructed of heavy gauge, polished stainless steel to maintain an attractive appearance after years of heavy use. Polyurethane foam insulation throughout ensures the ultimate in energy efficiency. The front shroud lifts up for easy access when cleaning the condenser unit.

## DOOR CONSTRUCTION

Each glass door is provided with a cylinder lock and ergonomically correct vertical handle. The door hinges are self-closing and have a hold-open feature at 120° which facilitates product loading. Proximity switches energize the recessed interior incandescent lighting when the door is opened. Humidity control wires around the door jamb prevent condensation from forming on the front of the cabinet in high humidity environments.

## REFRIGERATION SYSTEM

All components of the high efficiency, air-cooled, self-contained refrigeration system are mounted on top of the cabinet out of the food storage zone providing greater usable storage space. Environmentally friendly R-134a refrigerant is efficiently metered by a capillary system providing a constant, safe operating temperature and quick "recovery" under the most demanding conditions. The hermetically sealed systems are designed to operate from 40°F to 60°F. Each cooling coil has plasticized fin coils to resist food acids and dual-speed EC fan motor(s) for greater cooling capacity and efficiency. All condensate water is disposed of automatically by the energy efficient, non-electric condensate evaporator.

## INTERIOR STORAGE ARRANGEMENTS

7 fully extractable wine racks and one fixed rack on the bottom hold 10 bottles each for a total capacity of 80 bottles in the WC-1D-S1, and 160 bottles in the WC-2D-S1.

## V-TEMP™ CONTROL SYSTEM

The easy to use V-TEMP™ Control is standard. This durable, water resistant micro-processor monitors and controls the entire temperature maintenance process. It includes an ON/OFF switch, manual defrost, interior light switch, LED temperature indicator in °C or °F, a HI/LO audio/visual temperature alarm, power supply interruption, door ajar and "clean condenser" alarms. A manager's "lock-out" feature is provided to safeguard pre-determined control settings. A HACCP Event Indicator/Memory feature announces and records up to nine (9) alarm events. Unique to the V-TEMP™ are two standard modes of operation:

**SUPERCOOL** - Provides a lower "set-point" refrigeration condition for a set period of time when food has just been loaded into the refrigerator and needs to be quickly brought back down to a safe temperature.

**ENERGY SAVING** - The cabinet automatically reverts to the energy saving mode when there are no door openings for four hours.

**Note:** In order to provide peak operating performance the cabinet must have a 2 inch all around clearance and 12 inches above the top of the condensing unit. This ensures an adequate air supply and space for routine maintenance and/or service if required.

CHARACTERISTICS	1 Section	2 Section
Net Capacity	21.5	46.5
Width, Overall (in.)	26 1/2"	52 1/8"
Depth, Overall (inc. Handles)	35	35
Depth, Door(s) Open 90°	56 3/4"	56 3/4"
Clear Door Width (in.)	21 1/8"	21 1/8"
Clear Half-Door Height (in.)	25 3/8"	25 3/8"
Clear Full-Door Height (in.)	55 1/4"	55 1/4"
Height Overall (inc. 6" legs)	84 1/4"	84 1/4"
No. of Full Doors	1F	2D
No. of Full Extension Shelves	7	14
No. of Fixed Shelves	1	2

## ELECTRICAL DATA

Cabinet Voltage	115/60/1	115/60/1
Feed Wires	2	2
Condensing Unit Voltage	115/60/1	115/60/1
NEMA Plug	5-15P	5-15P
Total Amperes	9.8	10.7

**NOTE:** Plug style, voltage and full load amps may vary depending on certain options selected such as optional voltages and compressor upgrades.

## REFRIGERATION DATA

Condensing Unit Size	1/3 HP	1/3 HP
Refrigerant	R-134a	R-134a

CRATED DIMENSIONS	HT	Width	Depth	Cu. Ft.	Lbs.
One Section	84 1/2"	36	43	75.70	490
Two Section	84 1/2"	59 1/4"	43	124.59	820

\* Remote units use R-404A refrigerant standard and come with 6" legs

